



DJM-P Series 250w-280w

Poly II	DJM-250P	DJM-260P	DJM-270P	DJM-280P
Max power voltage	34.60	34.70	35.20	35.30
Max power current	7.23	7.49	7.67	7.93
Voc	42.90	43.03	43.65	43.77
Isc	8.57	8.51	8.59	8.76
Max Power	250	260	270	280
Module Efficiency	12.90%	13.42%	13.94%	14.45%
NOCT	47± 2°C			
Temp Coeff of Isc (%/°C)	0.05			
Temp Coeff of Voc (%/°C)	-0.35			
Temp Coeff of Pmp (%/°C)	-0.45			
Dimension	1957x990x50 mm			
Weight	25 kg			
No. of Cells	72 (6 x 12)			
Tolerance	± 3%			
Technology	Polycrystalline Cells 156 x 156 mm			
# of Bypass Diodes	6			
Operating Temperature	-40°C to + 85°C			
Storage Temperature	-40°C to + 85°C			
Max System Voltage	1000VDC(IEC)/ 600VDC(UL)			
Product Guarantee	5yrs free from defects in materials and workmanship			
Performance Guarantee	No less than 90% within 10 yrs and no less than 80% within 25 yrs			
Certificates	TUV(IEC61215&IEC61730), CE			

